

F2910

NB-IoT Terminal

TCP / UDP / MQTT /

V3.0.0



F2910 NB-IoT terminal is a kind of IOT device that provides data transfer by public NB-IoT network. It adopts high-performance industrial 32 bits CPU and embedded real time operating system. It supports RS232 and RS485 port that can conveniently and transparently connect one device to a NB-IoT network, allowing you connect to your existing serial devices with only basic configuration. It has low power consumption states. It has compatible 5 digital I/O channels, ADC, input pulse counter and pulse wave output function.

It has been widely used on M2M fields, such as wireless meter reading, smart city, smart grid, intelligent transportation, fire protection, asset tracking, mobile terminal POS, logistics, industrial automation, digital medical, military, agriculture, forestry, water, coal, petrochemical and other fields of data transmission.

HIGHLIGHT

INDUSTRIAL-GRADE DESIGN

- ◆ High-performance industrial cellular NB-IoT module
- ◆ High-performance industrial 32 bits CPU
- ◆ Low power consumption
- ◆ Embedded RTC circuit
- ◆ IP30 metal casting
- ◆ Certifications: CE

POWERFUL FUNCTIONS

- ◆ Supply 5 I/O channels, 2 analog inputs and 3 digital input/output
- ◆ Support multiple data centers and it can support 5 data centers at the same time
- ◆ Support dynamic domain name (DDNS) and IP access to data center
- ◆ Standard TCP/UDP/MQTT/COAP protocol stack, and support transparent data transmission.



Web: en.four-faith.com



Email: sales@four-faith.com



Tel: +86-592-5907276



11th Floor, A-06 Area, No.370, Chengyi Street, Jimei, Xiamen, Fujian, China

STABLE & RELIABLE

- ◆ Support hardware and software WDT
- ◆ Support auto recovery mechanism, including online detect, auto redial when offline to make it always online
- ◆ RS232/RS485 interface with built-in 15KV ESD protection
- ◆ SIM/UIM interface with built-in 15KV ESD protection
- ◆ Power interface with built-in phase-reversal and over-voltage protection
- ◆ Antenna interface with lightning protection(optional)

STANDARD INTERFACE &

EASY-TO-USE

- ◆ Adopt terminal block interface, convenient for industrial application
- ◆ Support standard RS232/RS485 that can connect to serial devices directly
- ◆ TTL logic level RS232 interface can be customized
- ◆ Support intellectual mode, enter into communication state automatically when powered
- ◆ Provide management software for remote management (optional)
- ◆ Multiple operating modes selection.

SPECIFICATIONS

NB-IoT

Bands	B3\ B5\ B8\ B20\ B28
Date Rate	100bps~100Kbps
Output Power	23±1dBm
Sensitivity	<-129dBm

HARDWARE

CPU	Industrial 32 bits CPU
FLASH	512KB (Extendable)
SRAM	256KB (Extendable)

INTERFACE

Serial	1*RS232 and 1*RS485 (or RS422) interface with built-in 15KV ESD protection Data bits: 8 bits Stop bits: 1 or 2 bits Parity bits: none, even or odd
Indicator	"Power", "ACT", "Online"
Antenna	1*Standard SMA female interface, 50 ohm, lightning protection(optional)
USIM	1*Standard sim card interface, support 1.8V/3V USIM card, 15KV ESD protection
Power	1*Terminal block interface, reverse-voltage and over-voltage protection

POWER SUPPLY

Standard	12V/0.5A
Range	DC: 5~36V

POWER CONSUMPTION

Standby	5~7mA@12V
Communication	15~20mA@12V
Sleep	1-2mA @12V
Deep Sleep	35-40uA@12V

PHYSICAL PROPERTIES

Casing	Metal, IP30
Dimensions	91x58.5x22mm
Weight	210g

OTHERS

Operating Temperature	-35~+75°C (-31~+167°F)
Storage Temperature	-40~+85°C (-40~+185 °F)
Relative Humidity	95% (non-condensing)
Certifications	CE



Antenna Interface



Terminal Block

Note: There may be differences between models of accessories and interfaces, actual products shall prevail.

ORDERING

Model	Description
F2910-B3	1800MHz, band3, Europe, Asia Pacific, Latin America and Sub-Saharan Africa
F2910-B5	850MHz, band5, China and South Korea
F2910-B8	900MHz, band8, China Europe and South Korea
F2910-B20	800MHz, band20, Europe
F2910-B28	700MHz, band28, Asia Pacific and Latin America



Web: en.four-faith.com



